

Safe Work Method Statement SWMS-403



SWMS Title:	Mopping of Floors		Description of Task / Activity:	Mopping of Floors		
Partner Site:	e: All Partner Sites					
SWMS prepared by: Darren Morris Pos		Position: Regional HSE Manager WA/SA/NT	Date: 07/11/2024	SWMS reviewed by: Jennifer Hoffman		
Authorisation:						
Authorised by	Operational Business	Unit Manager or Delegate	Date: 07/11/2024			

Elimination Substitution Engineering Administration

RISK ASSESSMENT PROCESS								
	Step 1 Determine Probability	Step 2						
	LIKELIHOOD	CONSEQUENCE						
	LIKELIHOOD	PERSON ASSETS		ENVIRONMENT				
A	Practically impossible	1	Minor Near Miss	Under \$500 Damage and Minimal Productivity Disruption.	No Damage			
В	Not Likely to Occur	2	First Aid Treatment Injury	\$500–1000 Damage and/or Slight Production Disruption.	Minor Damage			
С	Unusual but Possible	3	MTI or Short Term LTI	\$1000–5000 Damage and/or Production Disruption.	Reversible Damage			
D	Quite Possible	4	Long Term LTI	\$5000–10,000 Damage and/or Project Contingency Plan Required.	Serious Damage			
E	Almost Certain	5	Fatality, Permanent Disability	More than \$10,000 Damage and/or Large Reorganisation of Project.	Major Damage			

Risl	Risk Matrix							
		RISK ASSESSMENT PROCESS						
		Step 3 Calculate Risk						
				Conse	quence			
MENT		Likelihood	1	2	3	4	5	
age		А	1 Low	3 Low	6 Low	10 Medium	15 High	
nage		В	2 Low	5 Low	9 Medium	14 High	19 Extreme	
amage		С	4 Low	8 Medium	13 Medium	18 High	22 Extreme	
mage		D	7 Low	12 Medium	17 High	21 Extreme	24 Extreme	
nage		E	11 Medium	16 High	20 Extreme	23 Extreme	25 Extreme	

		Requir	ed PPE (Personal	Protective Equip	ment)		
				8		EY.	M
\boxtimes	\boxtimes	\boxtimes	\boxtimes				\boxtimes

SWMS No: HSEQ-SWMS-403

Process Area: Health, Safety, Environment & Quality



Safe Work Method Statement SWMS-403



1. Hazard / Hazardous Event	2. Current Controls
Mopping Floor – Slips as a result of the floor being wet due to spot mopping and muscoloskeletal injuries resulting from manual handling hazards.	 Only team members who have been made aware of the hazards associated with mopping are to carry out this task, this awareness training is to be recorded in the team member training register. Wet Floor/Cleaning in progress signs are to be displayed on all approaches to the area being mopped. For spot mopping follow the steps below; Wet floor/Cleaning in progress signs are to be displayed at all approaches to the area to be mopped. The Cleaning Trolley is to be used as a barrier to prevent access to the area. The Mop bucket is only to be filled to a half (1/2) full to prevent manual handling and splash hazards. When picking the bucket up ensure to use correct manual handling with knees bent and back straight. The Mop is to be used with a bucket and wringer; the mop is to be wrung out until damp (a minimum of 3 times). Mop the floor with the damp mop, and avoid bending or twisting of the back where possible. Once the spot mopping is complete, the area is to be dried using blue roll. Consider the use of a small type of electric, portable floor scrubber where mopping of large bathroom areas is required. Check the floor is dry. Once dry the warning signage can be removed. Never Leave a Wet/Damp Floor Unattended.
Hazardous Substances – For contact with all chemicals being used that are classified as a Hazardous Substance	 A Safety Data Sheet has been obtained for product being used. A risk assessment has been completed for any hazardous substance being used, Team members are to be briefed on their contents and the training recorded; see the Chemical SDS Register for Chemical Risk Assessments. Ensure PPE detailed in the SDS is worn. As a minimum this includes, rubber/latex gloves, goggles, non-slip footwear, long sleeve top and long pants.
Use of Hazardous Floor Stripping Solution	 Decant floor stripper in well ventilated areas away from other Team members. Use diluted solution of floor stripper (as per manufacturers recommendations) in well ventilated areas. Where skin contact with the floor cleaner occurs take off immediately all contaminated clothing and rinse skin with water or shower. If in eyes rinse cautiously with water for several minutes.



Safe Work Method Statement SWMS-403



Use of Tile Clean HD	 Deep cleaning and ad-hoc use of product only. Decant product using the chemical dispenser located in the cleaning room. Ensure product is diluted appropriately (20% chemical, 80% water) into a bucket. Ensure bucket is only filled to half to prevent splashes. Use product in well ventilated areas away from other team members. Where skin contact with the floor cleaner occurs take off immediately all contaminated clothing and rinse skin with water or shower. If in eyes rinse cautiously with water for several minutes. 				
Cleaning Solutions – Frequent immersing of hands into water-based cleaning solutions resulting in potential skin conditions	 Check your skin regularly for signs of Dermatitis (eczema); such as dryness, itching or redness, and report any concerns to your Manager, who should inform the Health, Safety & Environment Department of concern. Wear disposable non latex gloves when carrying out cleaning tasks. 				
3. Additional Information					
For Additional Information contact the HSE Team.					
4. Activity Risk Rating: Medium (B3)					

Process Area: Health, Safety, Environment & Quality